

Fail Safe Electro Bolt



Features

- Suitable for fully frameless glass door lock
- Low Temperature, safe & Durable
- Low Power, Environmental Protection
- Special Designed Solenoid for Strength and Long Life with 500000 Operations
- MOV Provides Reverse Current Protection
- The Intelligent form Jing Piece is Disposed, Three Magnitudes of Electric Current are Used
- Superior Strength Aluminum Alloy, Solid Stainless Steel Bolt
- Suitable for all Kind of the Door
- CE Certificate by European Union, MA China Public Security office
- Photoelectricity Control, Low Temperature
 - A: The Low Electric Current is Changed in the Twinkling of Eye;
 - B: Location on the Door is not Straight, The Door withstands the bolt, The Temperature will be low;
 - C: The Photoelectricity Controls Technology, Prevent the Trouble of the Machinery



Specification

Model	S-FGD
Fail Safe	Locked when energized
Face Plate	205Lx35WX41H(mm)
Strike	90Lx25Wx2H(mm)
Bolt	16mmDIA, stainless steel 16mm throw
Autolock Time Delay	0, 3, 6, 9sec
Signal Output	Door status Output, NC/COM
Voltage	DC12V
Start Current	900mA
Standby Current	150mA
Solid Bolt	Polishing housing, 800Kg Holding Force
Suitable For	Fully Frame Less Glass Door
Surface Temp	Low Temperature
Induction Distance	8mm
Operating temp	-20°C ~ 60°C
Operating Humidity	0~90%(non-condensing)
Special Designed	Tested to 500000 cycles
Face place material	High Aluminum Finished

Fail Safe Electro Bolt