



Supports



Mobile View

Features

- Compression algorithm upgraded to H.264 Main Profile. the advanced space-time filter technique makes the code stream lowered at least 30%
- Support main stream and extra steam encode synchronously.
- Mainstream is for local storage to maintain the Image quality, extra stream is for network real- time transmission to easily solve the bottle neck problem of bandwidth.
- Support all kinds of mobile monitor (iPhone, Windows Mobile, Blackberry, Symbian, Android)
- Support 3G & WIFI extension
- Completed protective circuit, unique treble watchdog function, make device never crashed

Specification



Model S-HIDVR-960-8

Operating System	Embedded LINUX
System Resource	Multi channel real-time recording synchronously, multi-channel real-time playback, multi-channel network operation, USB backup
Operating Interface	16-bit true color graphical menu interface and mouse support
Display Screen	1 / 4 / 8 / 9
Video Standards	PAL 25FPS / NTSC 30FPS
Image Coding	H.264
Playback Quality	960H / D1 / Hd1 / CIF / QCIF
Coding Capacity	8 Channel D1 / 960H
Ability to Decode	8 Channel D1 / 4 Channel 960H
Multi-mode Input	Local + Network Input: 4*D1+(1*1080P*+3*720P) Network Input: 16*D1/2*1080P+2*720P / 1*1080P +1*720P+ 6*960H / 8*720P
Motion Detection	Each screen can be set to 192 (16*12) detection area, multi-level sensitivity (local channel only)
Audio Compression	G.711A
Playback	8 Channel
Recording Mode	Manual / Alarm / Motion detection / Schedule
Recording Storage	Local HDD, Network
Search Mode	Point-in-time retrieval, calendar search, Event search, Channel search
Backup Mode	Local Backup, USB Mobile HDD, USB Burner, SATA Burner
Video Input	8 CH BNC
Video Output	1 CH BNC, 1VGA, 1CH HDMI, 1 CH Spot out
Audio Input	8 Ch RCA
Audio Output	1 Ch RCA
Alarm Input	8Ch
Alarm Output	1Ch
Network Interface	RJ45 10/100M adaptive Ethernet Port
PTZ Control	RS485, Support Multi PTZ Protocols
USB Interface	2 USB Port
Hard disk Interface	2 SATA interface (Max 2TB each)
WiFi	3G, WiFi (USB Extension)
Power	12V / 4A
Working Temperature	-10° C ~ +55° C
Working Humidity	10% ~ 90%

Hybrid 8 Channel SDVR

