



Virtual Central Locking System

Model S-A50

Defense zones	100 wireless and 8 wired
wireless remote control codes.	8
Display	Blue backlighting graphic display for clear information
groups	6 groups of voice alarm phones (mobile phone), and 2 groups of phones in alarm receipt center.
alarm logging	Built-in perpetual calendar and clock; automatic logging of alarm cases by time sequence.
Message recording playback	Human recording, synchronous playback for recording effect in audition.
More defense modes	Remote defense, keypad defense, and non-local remote defense by telephone; stay-in defense, timing defense, and individual defense in zones.
Programming of defense zone type	All zones could be programmed via keypad for immediate, delayed, 24-hour and bypass alarm modes.
Alarm Position Programming	Intelligent automatic speech recognition: SOS alarm, fire alarm, gas leak, magnetic contact alarm, hall alarm, window alarm, balcony alarm, and perimeter alarm
Timing defense and withdrawal	Console features automatic timing defense and withdrawal.
Intelligent Music Alarm	Full voice prompt. During defense at home, console music and voice alarm, external siren mute; during defense in the absence, console voice alarm, loud external siren alarm.
Password Recovery	Whether the console is in defense or withdrawal, the lost password can be recovered.
Intelligent learning code	Intelligent learning code, newly added with detector which is prompt and efficient, and convenient and simple.
Console status memory	Automatic console memory for defense and withdrawal, which could enable the console to automatically recover defense or withdrawal before power cut after the reset upon power cut or shut down.
Event Log Query	Console automatically records 45 pieces of all information concerning defense, withdrawal and alarm events.
Line priority alarm	Console will cut the busy call and switch to priority alarm in case of the alarm during ongoing call, no matter incoming or outgoing call.
Phone disconnection detection	Automatic detection and alarm warning in line disconnection, for anti-sabotage of telephone lines.
Remote control	Through remote phone (cell phone) dial-up, many operations could be realized, like defense, withdrawal and on-site monitoring by the console in the remote control form.
	Console is equipped with battery box, with optional AAA NI-HM rechargeable battery. Console meets 3C safety standards and national standard GB12663-2001
	Compatible with internationally accepted protocol of alarm receipt center: Ademco Contact ID alarm communication protocol.