



1080P IP Varifocal Dome IR Camera (Vandal Proof)



Features

- ★ Compression: H.264
- ★ Sensor: 1/2.5" Progressive Scan CMOS
- ★ Display Resolution: 2MP
- ★ Illumination: 0 Lux / F1.2 (IR ON)
- ★ Lens: 2.8 ~ 12 mm Varifocal
- ★ IR LED: 30 Pcs
- ★ IR Range: 10 ~ 25m



Model	S-2MP-DIRV
Sensor	1/2.5" Progressive Scan CMOS
OS	Embedded Linux System
Resolution	2MP
Illumination	0 LUX / F1.2 (IR ON)
Lens	2.8 ~ 12mm Varifocal
IR LED	30 Pcs
IR Range	10 ~ 25m
Compression	H.264
Synchronization	Internal
Electronic Shutter	1/1s~1/10,000s
Image Setting	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Image Frame Rate	25 / 30FPS
Systems	PAL / NTSC
Network Protocols	TCP/IP, HTTP, TCP, ICMP, DHCP, UDP, SMTP, FTP, DDNS & RTSP
ICR Function	Supported
White Balance	Auto
Static IP/DDNS	No Static IP, No DDNS Required
Multi Streaming	Supported
Password	Supported
POE	Optional
ONVIF	Compliant
Communication Interface	RJ45 10/100M
Operating Temperature	-20°C ~ +65° C
Humidity	95% Non-condensation
Power	DC 12V 1A

1080P IP Varifocal Dome IR Camera (Vandal proof)

