



2, 4 & 5MP H.264 Box Camera

S-CM-2M/S-CM-4M/S-CM-5M



Key Features

- 1/2.9" Progressive scan CMOS
- WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- On-board storage, up to 128GB
- Support Tripple stream
- Support Region of Interest(ROI)
- Support Defog
- Support NAS
- Support UPnP-TM
- Smart Functions

Supported Browser



IP Video Surveillance Solution

Specification	S-CM-2M	S-CM-4M	S-CM-5M	
Camera	Image Sensor		1/2.9" progressive scan CMOS	
	Electronic Shutter Speed		Auto/Manual, 1/3~1/10000s	
	Day/Night		Auto(ICR)	
	Lens		Optional	
Compression Standard	Video Compression		H.264	
	H.264 Codec profile		Main profile	
	Video Bit Rate		32 Kbps~9 Mbps	
	Audio Compression		G.711A	
Image	Max.resolution	1920*1080	2592*1520	2560*1920
	Frame Rate Main Stream	25fps (1920*1080)	25fps (2592*1520)	25fps (2560*1920)
	Frame Rate Sub Stream	D1/CIF 25fps		
	BLC	On/Off		
	ROI	Support		
	Defog	Support		
Network	Network Storage		NAS	
	Alarm Trigger		Motion detection, Intrusion detection, Line crossing, Network Disconnect, IP address conflict, Storage exception	
	Protocols		TCP/IP,ICMP,HTTP,FTP,DHCP,DNS,DDNS,RTP, RTSP,RTCP,NTP,UPnP,SMTP,UPnP-TM,P2P	
	System compatibility		Onvif 2.4,Profile S, CGI,Mobile Surveillance	
	Smart Phone		iPhone, Android	
Interface	Communication interface		1 RJ45 10M / 100M ethernet port	
	On-board storage		Support Micro SD/SDHC/SDXC slot, upto 128GB	
	Audio I/O		1/1	
	Alarm I/O		1/1	
	Reset button		Support	
General	WDR		Supported	
	POE		Built in POE	
	Power Supply / Consumption		DC12V ±10% / Max. 5W	
	Operating Conditions		-30 °C ~ 60 °C, Humidity 95% or less (non-condensing)	



| www.secureye.com

